



- NOTES:
1. ALL DIMENSIONS ARE IN INCHES [mm].
 2. FM AND FMc APPROVED. FOR USE IN CLASS 1 DIVISION 1 GROUP D AREAS.
 3. EXPLOSION PROOF CONTROL BOX MEETS NEMA 4 REQUIREMENTS.
 4. VAPORIZER PRESSURE VESSEL RATED AT 250 PSIG [17.6 KG/CM²] MAWP.
 5. VAPORIZER RELIEF VALVE SETTING 250 PSIG [17.6 KG/CM²].
 6. VAPORIZER CAPACITY RATED AT 0° F AND 100 PSIG PROPANE INLET CONDITION.
 7. SUITABLE FOR INDOOR/OUTDOOR INSTALLATION.
 8. VAPORIZER TO BE SECURED THROUGH THE FOUR MOUNTING HOLES ON ABOVE GROUND, LEVEL, SOLID, NON-COMBUSTIBLE BASE.
 9. AVOID DRY RUBBING OF THE INSULATION JACKET TO PREVENT ELECTROSTATIC CHARGING HAZARD. ALWAYS USE DAMP CLOTH FOR CLEANING.
 10. ECONOMY VALVE OPTION AVAILABLE UPON REQUEST.
 11. APPROXIMATE SHIPPING WEIGHT. TX25-100 (128lbs.) TX160 (145lbs.) TX240 (155lbs.) TX320 (173lbs.)

THIRD ANGLE PROJECTION 	TOLERANCES UNLESS OTHERWISE SPECIFIED .X ± .XX ± .XXX ± ANGLE ±0°30' FRACTIONS ± 1/4"	 151 S. Michigan St., Seattle, Washington, USA 98108 Tel: (206) 789-5410 Fax: (206) 789-5414	Drawn By: RWP
			Checked By: DN
DO NOT SCALE DRAWING	INTERPRET THIS DRAWING IN ACCORDANCE WITH ANSI/ASME Y14.5-2009	Part #	Approved By:
THIS DRAWING SHALL NOT BE REPRODUCED OR USED IN ANY MANNER DETRIMENTAL TO ITS INTERESTS. ALL RIGHTS RESERVED. © COPYRIGHT ALGAS-SDI	Title:	Date: 10/20/06	Scale: 1:12 AND NOTED
Size: B	Dwg. #	Job #	Rev.: D
TORREXX SERIES ELECTRIC VAPORIZER - STANDARD		5001-6001	Sht. No.: 1 of 1