



**NOTES:**

1. ALL DIMENSIONS ARE IN mm [INCHES].
2. CONFORMS TO HAZARDOUS AREA RATING: EEx d II B T3/ Ex II 2G-DNV 06 ATEX Q166Q.
3. PRESSURE VESSEL CONFORMS TO PRESSURE EQUIPMENT DIRECTIVE: 40065-2011-CE-USA-DNV REV 1.
4. CE COMPLIANT.
5. VAPORIZER PRESSURE VESSEL RATED AT 250 PSIG [17.6 KG/CM<sup>2</sup>] MAWP.
6. RELIEF VALVE SETTING 17.24 BARG (250PSIG).
7. VAPORIZER CAPACITY RATED 0° F AND 100 PSIG PROPANE INLET CONDITION.
8. SUITABLE FOR INDOOR/OUTDOOR INSTALLATION.
9. VAPORIZER TO BE SECURED THROUGH THE FOUR MOUNTING HOLES ON ABOVE GROUND, LEVEL, SOLID, NON-COMBUSTIBLE BASE.
10. AVOID DRY RUBBING OF THE INSULATION JACKET TO PREVENT ELECTROSTATIC CHARGING HAZARD. ALWAYS USE DAMP CLOTH FOR CLEANING.
11. ECONOMY VALVE OPTION AVAILABLE UPON REQUEST.
12. APPROXIMATE SHIPPING WEIGHT: TX25-100 (58kg) TX160 (66kg) TX240 (70kg) TX320 (79kg).

THIRD ANGLE PROJECTION



DO NOT SCALE DRAWING

INTERPRET THIS DRAWING IN ACCORDANCE WITH ANSI/ASME Y14.5-2009  
 THIS DRAWING SHALL NOT BE REPRODUCED OR USED IN ANY MANNER DETRIMENTAL TO ITS INTERESTS. ALL RIGHTS RESERVED.  
 © COPYRIGHT ALGAS-SDI

**TOLERANCES**

UNLESS OTHERWISE SPECIFIED

.X ±  
 .XX ±  
 .XXX ±

ANGLE ±0°30'  
 FRACTIONS ± 1/16"



151 S. Michigan St., Seattle, Washington, USA 98108  
 Tel: (206) 789-5410 Fax: (206) 789-5414

Part #

Drawn By: RWP

Checked By: DN

Approved By:

Date: 10/23/06

Scale: 1:12 AND NOTED

Job # A.S.D.I. STD.

**TORREXX SERIES ELECTRIC VAPORIZER- NEMKO**

Size: **B**

Dwg. #

**5001-6003**

Sht. No.: 1 of 1

Rev.: **D**