


NOTES:

1. ELECTRICAL: 1PH 110-277VAC, 3PH 4 WIRE WYE 173-480 VAC, 50/60Hz
2. CONFORMS TO HAZARDOUS AREA RATING:
 1. IECEx/ATEX Ex db IIA T3 Gb
 2. UL: CLASS I, DIV 1, GROUP D T3
3. ENCLOSURE: TYPE 4, HORIZONTAL OR VERTICAL MOUNT
4. RELIEF VALVE SET: 250 PSIG [17,24 BAR]
5. MAWP: 250PSIG AT 300°F [17,24 BARG AT 149°C]
 MDMT: -20°F [-29°C] AT 250 PSIG [17,24 BAR]
6. WEIGHT: 140 LB [77 KG]
7. DIMENSIONS SHOWN IN INCHES [MM]

THIRD ANGLE PROJECTION  DO NOT SCALE DRAWING	TOLERANCES UNLESS OTHERWISE SPECIFIED .X ± 0.10 .XX ± 0.030 .XXX ± 0.010 ANGLE ± 1° FRACTIONS ± 1/4"	 151 S. Michigan St., Seattle, Washington, USA 98108 Tel: (206) 789-5410 Fax: (206) 789-5414	Drawn By: AAS
			Checked By: DN
INTERPRET THIS DRAWING IN ACCORDANCE WITH ANSI/ASME Y14.5-2009.		Part # N/A	Approved By:
THIS DRAWING IS PROPRIETARY AND CONFIDENTIAL AND SHALL NOT BE REPRODUCED OR USED IN ANY MANNER DETRIMENTAL TO ALGAS-SDI'S INTERESTS. ALL RIGHTS RESERVED. © COPYRIGHT ALGAS-SDI		Title: Z100 & Z150 EQUIPMENT DRAWING	Date: 1/31/2018
Size: B	Dwg. # 0903-6002	Sht. No.: 1 of 1	Rev.: C