



- NOTES:
1. ALL DIMENSIONS ARE IN INCHES [mm].
 2. VAPORIZER PRESSURE VESSEL RATED AT 290 PSIG [20 BAR] MAWP.
 3. VAPORIZER RELIEF VALVE SETTING 250 PSIG [17.2 BAR].
 4. cULus APPROVED.
 5. CE MARKED (PED).
 6. VAPORIZER CAPACITY AT 0°F AND 100 PSIG PROPANE INLET CONDITION 160 GPH [320 KG/HR].
 7. VAPORIZER TO BE SECURED THROUGH THE FOUR MOUNTING HOLES ON ABOVE GROUND, LEVEL, SOLID, NON-COMBUSTIBLE BASE.
 8. HEAT INPUT 180,000 BTU/HR [189,910 KJ/HR].
 9. USE THE 1/8" FNPT PORT TO PIPE AWAY 1ST STAGE VENT IF REQUIRED.
 10. USE THE 3/4" FNPT PORT TO PIPE AWAY 2ND STAGE VENT IF REQUIRED.
 11. APPROXIMATE SHIPPING WEIGHT 425 LBS [193 KG].

THIRD ANGLE PROJECTION DO NOT SCALE DRAWING INTERPRET THIS DRAWING IN ACCORDANCE WITH ANSI/ASME Y14.5-2009 THIS DRAWING SHALL NOT BE REPRODUCED OR USED IN ANY MANNER DETRIMENTAL TO ITS INTERESTS. ALL RIGHTS RESERVED. © COPYRIGHT ALGAS-SDI	TOLERANCES UNLESS OTHERWISE SPECIFIED .X ± .XX ± .XXX ± ANGLE ±0°30' FRACTIONS ± 1/4"	 151 S. Michigan St., Seattle, Washington, USA 98108 Tel: (206) 789-5410 Fax: (206) 789-5414	Drawn By: M. KRASS Checked By: DN Approved By:
			Date: 3/31/10 Scale: 1:24 AND NOTED Job # A.S.D.I. STD.
LARGE DF 160H VAPORIZER EQUIPMENT DRAWING			Part # Size: B Dwg. # 1508-6001 Sht. No.: 1 of 1 Rev.: D