



NOTES:

1. ALL DIMENSIONS ARE IN mm [INCHES].
2. NEMKO APPROVED FOR USE IN ZONE 1 AREAS.
3. DNV APPROVED FOR CONFORMANCE WITH PRESSURE EQUIPMENT DIRECTIVE.
4. CE COMPLIANT.
5. VAPORIZER PRESSURE VESSEL RATED AT 250 PSIG [17.6 KG/CM²] MAWP.
6. RELIEF VALVE SETTING 17.24 BARG (250PSIG).
7. VAPORIZER CAPACITY RATED 0° F AND 100 PSIG PROPANE INLET CONDITION.
8. SUITABLE FOR INDOOR/OUTDOOR INSTALLATION.
9. VAPORIZER TO BE SECURED THROUGH THE FOUR MOUNTING HOLES ON ABOVE GROUND, LEVEL, SOLID, NON-COMBUSTIBLE BASE.
10. AVOID DRY RUBBING OF THE INSULATION JACKET TO PREVENT ELECTROSTATIC CHARGING HAZARD. ALWAYS USE DAMP CLOTH FOR CLEANING.
11. ECONOMY VALVE OPTION AVAILABLE UPON REQUEST.
12. APPROXIMATE SHIPPING WEIGHT: TX25-100 (58kg) TX160 (66kg).

THIRD ANGLE PROJECTION



DO NOT SCALE DRAWING

INTERPRET THIS DRAWING IN ACCORDANCE WITH ANSI/ASME Y14.5-2009

THIS DRAWING SHALL NOT BE REPRODUCED OR USED IN ANY MANNER DETRIMENTAL TO ITS INTERESTS. ALL RIGHTS RESERVED.

© COPYRIGHT ALGAS-SDI

TOLERANCES

UNLESS OTHERWISE SPECIFIED

.X ±

.XX ±

.XXX ±

ANGLE ±0°30'

FRACTIONS ± 1/4"



151 S. Michigan St., Seattle, Washington, USA 98108
Tel: (206) 789-5410 Fax: (206) 789-5414

Part #

TORREXX SERIES ELECTRIC VAPORIZER- NEMKO

Size: **B**

Dwg. #

5001-6003

Sht. No.: 1 of 1

Rev.: **H**

Drawn By: RWP

Checked By: BDZ

Approved By:

Date: 10/23/2006

Scale: 1:12 AND NOTED

Job # TORREXX