



- NOTES:
1. ALL DIMENSIONS ARE IN mm [INCHES].
 2. NEMKO APPROVED FOR USE IN ZONE 1 AREAS.
 3. DNV APPROVED FOR CONFORMANCE WITH PRESSURE EQUIPMENT DIRECTIVE.
 4. CE COMPLIANT.
 5. VAPORIZER PRESSURE VESSEL RATED AT 250 PSIG [17.6 KG/CM²] MAWP.
 6. RELIEF VALVE SETTING 17.24 BARG (250PSIG).
 7. VAPORIZER CAPACITY RATED 0° F AND 100 PSIG PROPANE INLET CONDITION.
 8. SUITABLE FOR INDOOR/OUTDOOR INSTALLATION.
 9. VAPORIZER TO BE SECURED THROUGH THE FOUR MOUNTING HOLES ON ABOVE GROUND, LEVEL, SOLID, NON-COMBUSTIBLE BASE.
 10. AVOID DRY RUBBING OF THE INSULATION JACKET TO PREVENT ELECTROSTATIC CHARGING HAZARD. ALWAYS USE DAMP CLOTH FOR CLEANING.
 11. ECONOMY VALVE OPTION AVAILABLE UPON REQUEST.
 12. APPROXIMATE SHIPPING WEIGHT: TX240 (121kg) TX320 (130kg).

THIRD ANGLE PROJECTION 	TOLERANCES UNLESS OTHERWISE SPECIFIED .X ± .XX ± .XXX ± ANGLE ± 1° FRACTIONS ± 1/4"	<p>151 S. Michigan St., Seattle, Washington, USA 98108 Tel: (206) 789-5410 Fax: (206) 789-5414</p>	Drawn By: RWP
			Checked By: BZ
DO NOT SCALE DRAWING	INTERPRET THIS DRAWING IN ACCORDANCE WITH ANSI/ASME Y14.5-2009	Part #	Approved By:
THIS DRAWING SHALL NOT BE REPRODUCED OR USED IN ANY MANNER DETRIMENTAL TO ITS INTERESTS. ALL RIGHTS RESERVED. © COPYRIGHT ALGAS-SDI	Title:	TORREXX SOLID STATE RELAY VAPORIZER - NEMKO	Date: 10/29/2020
Size: B	Dwg. #	5001-6011	Scale: 1:16 AND NOTED
	Sht. No.: 1 of 1		Rev.: A