

## TORREXX CE Electric Vaporizer Data Sheet

MODEL	PHASE	VOLTAGE (VAC)	CURRENT (A)	HEATER RESISTANCE (OHMS)	WIRE-TO-WIRE RESISTANCE (OHMS)	NOMINAL POWER (kW)
TX25	1	120	32.8	22.2	3.7	3.9
TX25	1	208	14.2	22.2	14.8	3.0
TX25	1	220	15.0	22.2	14.8	3.3
TX25	1	240	16.4	22.2	14.8	3.9
TX50	1	208	28.5	22.2	7.4	5.9
TX50	3	208	16.4	22.2	14.8	5.9
TX50	1	220	30.1	22.2	7.4	6.6
TX50	3	220	17.4	22.2	14.8	6.6
TX50	1	240	32.8	22.2	7.4	7.9
TX50	3	240	19.0	22.2	14.8	7.9
TX50	3	380	10.0	22.2	44.3	6.6
TX50	3	400	10.6	22.2	44.3	7.3
TX50	3	415	10.9	22.2	44.3	7.8
TX100	1	208	56.9	22.2	3.7	11.8
TX100	3	208	32.8	22.2	7.4	11.8
TX100	1	220	60.2	22.2	3.7	13.2
TX100	3	220	34.7	22.2	7.4	13.2
TX100	1	240	54.7	22.2	4.4	13.1
TX100	3	240	37.8	22.2	7.4	15.7
TX100	3	380	20.0	22.2	22.2	13.2
TX100	3	400	21.1	22.2	22.2	14.6
TX100	3	415	21.9	22.2	22.2	15.7
TX100	3	440	17.4	22.2	29.6	13.2
TX100	3	480	19.0	22.2	29.6	15.8
TX160	3	208	45.5	16	5.3	16.4
TX160	3	220	48.1	16	5.3	18.3
TX160	3	240	52.5	16	5.3	21.8
TX160	3	380	27.8	16	16	18.3
TX160	3	400	29.3	16	16	20.3
TX160	3	415	30.3	16	16	21.8
TX160	3	440	24.0	16	21.3	18.3
TX160	3	480	26.2	16	21.3	21.8
TX240	3	380	38.6	11.5	11.5	25.4
TX240	3	400	40.6	11.5	11.5	28.1
TX240	3	415	42.1	11.5	11.5	30.3
TX240	3	440	33.4	11.5	15.3	25.5
TX240	3	480	36.4	11.5	15.3	30.3
TX320	3	380	58.7	7.4	7.7	38.6
TX320	3	400	53.4	8.8	8.8	37.0
TX320	3	415	55.4	8.8	8.8	39.8
TX320	3	440	50.8	7.4	10.3	38.7
TX320	3	480	48.0	8.8	11.7	39.9